



DECLARATION OF PERFORMANCE

No. 204CPR2013-07-01

1. Unique identification code of the product-type: **bauroc THIN LAYER MORTAR EN 998-2 T-M10**
2. Intended use/es: **Designed thin layer mortar for AAC products in elements (external and internal) subjected to structural requirements**
3. Manufacturer: **SAKRET OÜ, Mäo küla, Paide vald, 72751 Järvamaa, Estonia. Phone: (+372) 3846 600, e-mail: info@sakret.ee**
4. Authorised representative: **Not applicable**
5. System/s of AVCP: **System 2+**
- 6a. Harmonised standard: **EN 998-2:2017**

Notified body/ies: **SIA Certification centre of the Latvian Academy of Sciences, No. 1327, Akademijas square, 1-602. Riga, Latvia**

7. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Compressive strength:	M10	EN 998-2
Correction time:	10 min.	
Water absorption:	$\leq 0,1 \text{ kg}/(\text{m}^2 \cdot \text{min}^{0,5})$	
Water vapour permeability (μ):	5/20	
Initial shear strength:	$\geq 0,30 \text{ N}/\text{mm}^2$	
Contents of chloride:	$\leq 0,1 \%$	
Durability (freeze/thaw resistance):	F35	
Thermal conductivity ($\lambda_{10\text{dry}}$)	$\leq 0,47 \text{ W}/(\text{mK}) \text{ P}=50\%$ $\leq 0,54 \text{ W}/(\text{mK}) \text{ P}=90\%$	
Reaction to fire:	A1	

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Sirle Eelma

Technologist
Paide, 11.10.2017